

# **190 MIG WELDER**

CAT# 318	Processes	Input Power	Amperage Range	Wire Diameter Range	Rated Output	Plate Thickness Range	Weight	Dimensions
QUICK	MIG (GMAW)	230V	35-190A	.024″035″	120A@25% Duty Cycle	24 ga 3/8"	63 lbs.	19″ x 9.5″ x 16.5″
SPECS	Flux Cored (FCAW)							



### **FEATURES AND BENEFITS:**

- Ease of Use Euro Connect Torch with Tweco® style consumables Easy to disconnect to swap out torch or change liner
- Better wire feeding

Upgraded cast aluminum wire drive system Dual geared idler and drive roll with better de-spooler

- More space Larger cabinet for easy access to 4" (1-2 lbs.) and 8" (10-11 lbs.) spools
- Improved Design Integrated feet Torch wrap included for cable organization Torch with built in strain relief, which extends cable life
- Larger Work Envelope 10' torch and 15' power cord increase the work area

#### Includes:

MIG gun with 10' lead 10' Ground cable & clamp Gas hose and regulator 15' Input power cable

#### **Applications:**

DIY **Metal Fabrication** Maintenance & Repair Farm & Ranch Automotive

**Reliable Technology:** Easy to use

## Warranty:

Protected under our industry leading

5/3/1 WARRANTY

#### FORNEY INDUSTRIES 5/3/1 WARRANTY:

5 years: Original main power rectifiers only to include SCRs, diades and discrete rectifier modules, transformers, stabilizers and reactors.
3 years: Drive systems, PC boards, motors,

- switches and controls
- 1 year: MIG guns, relays, contractors and regulators, plasma cutting torches, and accessories.



DUTY CYCLE	AMPS		
15%	140A		
25%	120A		
<b>60</b> %	80A		
100%	60A		

P-10805



Contact us at www.forneyind.com or Customer Service at 1-800-521-6038 Got Questions? Visit askforney.com



Contact us at www.forneyind.com or Customer Service at 1-800-521-6038 Got Questions? Visit askforney.com

